

# Specification

<b>Customer</b> 9999	<b>Contact Information</b>
General Specification	Quality Department Dr. Konrad Rockstein Phone: +49 69 365054-187 E-Mail: konrad.rockstein@orioncarbons.com

<b>PRINTEX® XE2 B BEADS</b>	
<b>Material Code</b>	120000072
<b>Packaging Information</b>	5 KG POLY BAG 195 KG
<b>Date of Issue</b>	15-OCT-12
<b>Revision</b>	01
<b>Customer Material Code</b>	

Characteristic	Unit	Reference	Min	Target	Max
Sieve residue 45 µm, DIN (ppm)	ppm	ISO 787_18			500
Sulfur Content	%	ASTM D1619			0.80
Iodine Adsorption Number	g/kg	ASTM D1510	1,025.0	1,125.0	1,225.0
Ash Content	%	ASTM D1506			2.00
Oil Absorption Number	cc/100	ASTM D2414	380.0	420.0	460.0
Heating Loss (105°C)	%	ISO 787_2			1.00
pH		ASTM D1512	6.3	7.8	9.3

All warranty claims in respect of the conformance of our product are subject to the liability limitations stipulated in our "General Terms and Conditions of Sale and Delivery". The data listed above only reflects the criteria for our internal quality tests. No modification or extension of liability results there from. By providing such data, we do not make any express or implied warranty, whether for specific properties of the product or for fitness for any particular application or purpose. All values are valid for the product only at the time when the product is dispatched from the plant.