

(old: Foamaster[®] ENA-2)



general	liquid defoamer for emulsion paints and adhesives systems
chemical nature	blend of hydrocarbons and non-ionic surfactants
Properties	
physical form	turbid, amber liquid
shelf life	When stored under the usual appropriate storage conditions, the product can be stored for 1 year
storage	During storage of Foamaster [®] MO 2127 a slight sedimentation / phase separation might occur. The defoaming properties of Foamaster [®] MO 2127 are not affected, if the product is mixed thoroughly prior to use.
typical properties (no supply specification)	density at 20 °C (68 °F)~ 0.90/cm³Brookfield viscosity at 23°C (73°C)~ 600 mPas
Application	
	Foamaster [®] MO 2127 is a defoamer for emulsion paints based on styrene-butadiene, acrylic and its copolymers, ethylene-vinyl acetate and water-soluble alkyds.
recommended concentrations	usually 0.2 – 0.5% calculated on total formulation.

Safety

When handling this product please comply with the advice and information given in the safety data sheet and observe protective and workplace hygiene measures adequate for handling chemicals.

Note

The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our product, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the product for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights, etc. given herein may change without prior information and do not constitute the agreed contractual quality of the product. The agreed contractual quality of the product results exclusively from the statements made in the product specification. It is the responsibility of the recipient of our product to ensure that any proprietary rights and existing laws and legislation are observed.

 $^{(\!8\!)}$ = registered trademark, TM = trademark of BASF Group, unless otherwise noted

BASF SE Performance Additives 67056 Ludwigshafen, Germany www.basf.com/resins

service-edc@basf.com